Traka Touch Pro L

Specifications



Introducing the Traka Touch Pro L. The next evolution in the proven Traka Touch range.

Built on the successful, market-leading Traka Touch range, Touch Pro is a more secure, durable and cost-effective solution that looks as good as it performs.

Traka Touch Pro is our most secure cabinet to date. It is built to last, built for simplicity, built for flexibility and built with sustainability in mind. A triple-layer outer, scratch-resistant door and metal panelling are some security features to ensure the Traka Touch Pro L is less vulnerable to attack.

The Touch Pro has improved height and depth, providing extra room and a better way to organise and manage keys. A new sleek modern, modular design offers a universal appeal and fits different environments, making it quick and easy to assemble, install and configure.

General ___

- Keys are readily available 24/7
- Access by authorised users only
- 7" capacitive touch screen for accurate input
- Full audit trail of all users and key transactions
- Securely store and manage up to 180 keys (or up to 360 keys using double-density strips) in 1 unit, or up to 720 keys using extension units
- Easy access via PIN code, card reader and /or biometric fingerprint reader
- Battery backup
- Soft close-down with no data loss in the event of long term power failure

Standalone _

- Cutting edge key management solution that operates entirely independently of your IT system
- Standalone 'plug and play' system
- No network, PC or external connection required
- USB port for import/export of reports via memory stick
- Automatic data backup to removable SD card



Network

- Full network capability and management through TrakaWEB
- · Centralised administration and reporting
- Browser based for remote administration

Optional Features _

- Item booking
- Reason/fault logging
- Access schedules

Specifications

Mechanical data	
Height:	1939.7mm / 76.37"
Width:	846mm / 33.31"
Depth:	160mm / 6.3"
Weight:	79.5kg / 175.71 lb

Material data	
Cabinet material:	Aluminium
Colour:	RAL7021 - Black grey
Door material:	Clear polycarbonate or solid metal

Electrical data	
Power supply:	Input: 100-240V AC, Output: 15V DC
Battery backup:	DC12V 7Ah (H) 97.5mm x (W) 65mm x (L) 151mm / (H) 3.84" x (W) 2.56" x (L) 5.94"
Power consumption:	35W max, typical 7W idle

Environmental data	
IP rating:	N/A
Operating temp:	Ambient, for indoor use only (-5°C to +40°C / +23°F to +104°F at 95% non-condensing relative humidity)
Mounting:	Wall
Key positions:	10-180 (or up to 360 using double density strips) in 1 unit; up to 720 using extension units
Receptor strip support:	Locking, non-locking, with buttons, without buttons, double density (360 positions), combination of both – all with Tri-colour LEDs

Network & connectivity data	
Users per system:	Up to 40,000
Communications:	Ethernet (TCP/IP) 10/100 MB
Reader interface:	Clock/data, Wiegand, Serial (RS232/ TTL), PIN only, OSDP Readers (RS485) with or without encryption
Alarm interface:	3x1A/24V dry contact relay contacts for connecting to alarms, access control or CCTV systems

Conformity & Standards data	
Certifications:	UKCA, CE, FCC, CSA, ICES
Environmental:	RoHS & WEEE Compliant

For more information on Traka and the benefits of intelligent key cabinets, please visit traka.com

traka.com